

Note:

1: Material(材料) :

Barrel: Brass C3602 (针管: 黄铜 C3602)
 Plunger: Brass C3604 (针头: 黄铜 C3604)
 Spring: SUS304 (弹簧: 不锈钢线 SUS304)

2: Plating(电镀) :



Barrel: 1u' Au over 50~80u' Ni(针管: 镀金1u', 镍底50~80u'.)
 Plunger: 1u' Au over 50~80u' Ni (针头: 镀金1u', 镍底50~80u'.)
 Spring: 1u' Au over 20~50u' Ni (弹簧: 镀金1u', 镍底20~50u')

3: Electrical(电气特性):

Rated Current & Voltage: DC 12V;1A (额定电压&电流: 直流12,1A)
 Contact Resistance: 50 mohm Max. at working height.
 接触电阻: 最大50毫欧 (在工作高度状态下)

4: Mechanical(机械性能):

Force: 68±20%gf at working height. (68±20%gf 在工作高度)
 Full stroke:1.6mm (全冲程: 1.6mm)
 Durability: 20000 cycles(min) (寿命: 20000次)

DWG. NO.	ZXS-2278A	DESIGNED BY:		SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		 东莞市深茂精密电子有限公司 http://www.gdshenmao.com/ TEL: 0769-81629844 FAX: 0769-81669504
TITLE:	2.0x2.2x3.0x1.3x6.6	CHECKED BY:		SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	
		APPROVED BY:		DATE:	12.28.2018	VER.	A.0	X.XX ±0.05mm	X.XX ±0.50°	
								X.X ±0.10mm	X.X ±1.00°	
								X. ±0.20mm	X. ±2.00°	